1 <u>TITLE OF THE INVENTION</u>

2 "ADDRESS CONVERTER FOR GATEWAYS INTERCONNECTING

3 NETWORKS OF DIFFERENT ADDRESS FORMATS"

4 <u>BACKGROUND OF THE INVENTION</u>

5 <u>Field of the Invention</u>

6 The present invention relates generally to address

7 conversion and more specifically to conversion of address data

8 contained in a packet when the packet travels between networks

9 of different address formats.

10 <u>Description of the Related Art</u>

11 Address conversion is necessary for a gateway when routing a

12 packet from a first network to a second network if the address

13 formats of the networks are different from each other. For

14 example, in an internetwork environment, local private networks

15 are connected to remote private networks via a global network. In

16 such configurations, addresses of the private networks are

17 organized independently of those assigned by the global network

18 in order to facilitate address management of the private networks.

19 An address converter disclosed in Japanese Laid-Open

20 Patent Specification 09-233112 uses a database that maps

21 addresses of a first network to corresponding addresses of a second

22 network. When the address converter receives a packet from the

23 first network, it makes a search through the database for the

24 corresponding address data of the second network that is mapped

25 to the address data contained in the packet. However, if the

26 amount of data contained in the database increases with an

27 increasing number of users, the time taken to search through the

28 database becomes substantial. Hence, there is a significant

29 amount of latency in the transmission of packets across different

30 networks.

31 <u>SUMMARY OF THE INVENTION</u>

32 It is therefore an object of the present invention to provide

NE-964

- 2 -

1 a method of packet transmission and an address converter for
2 reducing the latency of packets travelling across first and second
3 networks of different address formats.
4 　　The stated object is achieved by transmitting second address
5 data conforming to the second network with first address data
6 that conforms to the first network.
7 　　According to a first aspect of the present invention, there is
8 provided a method of transmitting packets between first and
9 second networks of different address formats, comprising the
10 steps of (a) receiving, from a first network, a packet containing
11 first address data conforming to the first network and second
12 address data conforming to a second network, the first address
13 data being contained in a packet header of the packet and the
14 second address data being contained in an auxiliary header of the
15 packet, (b) rewriting the first address data with the second address
16 data, and (c) transmitting the packet to the second network.
17 　　According to a second aspect of the present invention, there
18 is provided an address converter for use in a gateway connected
19 between first and second networks of different address formats,
20 comprising receive means for receiving, from the first network, a
21 packet containing first address data formulated according to the
22 first network and second address data formulated according to the
23 second network, the first address data being contained in a packet
24 header of the packet and the second address data being contained
25 in an auxiliary header of the packet. Control means is provided
26 for rewriting the first address data of the packet with the second
27 address data of the packet. Transmit means transmits the packet
28 to the second network.
29 　　　BRIEF DESCRIPTION OF THE DRAWINGS
30 　　The present invention will be described in further detail
31 with reference to the accompanying drawings, in which:

1   Fig. 1 is a block diagram of a communication system in
2   which the gateway of the present invention is shown
3   interconnecting networks of different address formats;
4   Fig. 2 shows the data format of a packet used in the present
5   invention;
6   Fig. 3 is a flowchart of the operation of the controller of
7   Fig. 1 when performing an address conversion on an incoming
8   packet according to a first embodiment of the present invention;
9   Figs. 4A and 4B are illustrations of the register during
10   address conversion according to the first embodiment;
11   Fig. 5 is a flowchart of the operation of the controller when
12   performing an address conversion on an incoming packet
13   according to a second embodiment of the present invention; and
14   Figs. 6A and 6B are illustrations of the register during
15   address conversion according to the second embodiment.

16   ## DETAILED DESCRIPTION

17   Fig. 1 illustrates a gateway 10 of the present invention for
18   interconnecting networks 11 and 12 via communication links 13
19   and 14. The address format of each network is different from the
20   address format of the other, and for this reason, the gateway 10
21   includes a pair of address converters 21 and 22 of identical
22   construction, each for a particular direction of transmission.
23   Specifically, the address converter 21 provides address conversion
24   on signals received from the network 11 via an interface unit 20 to
25   the network 12 via an interface unit 23, the address converter 22
26   providing address conversion on signals received from the network
27   12 via interface unit 23 to the network 11 via interface unit 20.
28   As shown in detail, the address converter 22 includes an
29   input buffer 30 for buffering incoming packets from the link 14,
30   and a register 31 for storing a packet from the input buffer 30 on a
31   one-at-a-time basis. A controller 32 is provided for making a
32   search through the register 30 for target address data when a

- 4 -

1 packet is stored. Controller 32 performs conversion of the
2 packet's address data using the target address data and formulates
3 an outgoing packet in a manner as will be described in detail later,
4 and forwards the outgoing packet to an output buffer 34 where
5 the packet is buffered and transmitted to the link 13.

6   An address conversion table 33 is also connected to the
7 controller 32 to be used when the target address data is not found
8 in the received packet. Address conversion table 33 maps the
9 address data of a network to corresponding address data of another
10 network.

11   As shown in Fig. 2, the packet of the present invention is
12 divided into a packet header (such as Ipv6 header), an auxiliary
13 header following the packet header and a payload field. The
14 packet header consists of a destination address (DA_1) field 41, a
15 source address (SA_1) 42 and a remainder field 43 for mapping
16 other header information. The original destination and source
17 addresses DA_1 and SA_1 are conforming to the format of the
18 source network.

19   According to the present invention, the auxiliary header
20 includes a target address field and an auxiliary information field.
21 The target address field is divided into subfields 44, 45 and 46 for
22 respectively mapping a field indicator FI_1 for specifying the
23 auxiliary header, a target destination address (DA_2) and a target
24 source address (SA_2). The target destination and source addresses
25 DA_2 and SA_2 are conforming to the format of the destination
26 network. The auxiliary information field is divided into subfields
27 47 and 48 for respectively mapping a field indicator FI_2, which
28 specifies the auxiliary information field 48, and auxiliary
29 information. The auxiliary information field 48 is followed by a
30 payload field 49 in which payload bits are placed.

31   According to a first embodiment of the present invention,
32 the operation of the controller 32 of each address converter

NE-964

- 5 -

1 proceeds according to the flowchart of Fig. 3.

2   When an incoming packet is received in the input buffer 30
3 and then transferred to the register 31 (step 301), the contents of
4 the packet are stored in storage locations 51 to 59 of the register
5 as shown in Fig. 4A corresponding to fields 41 to 49 of the packet.

6   The controller 32 proceeds to step 302 to make a search
7 through the register 31 to determine if there is an auxiliary header
8 to determine (step 303). If there is none, the decision at step 303
9 is negative and the controller proceeds to step 306 to perform an
10 address conversion on the incoming packet using the conversion
11 table 33 and forwards the address-converted packet to the output
12 buffer 34 (step 308) and proceeds to the end of the routine.

13   If the decision at step 303 is affirmative, the controller
14 proceeds to step 304 to make a search through the auxiliary header
15 to determine if it contains a target address field (step 305). If
16 there is none, the controller proceeds to step 306.

17   If target address data is contained in the auxiliary header,
18 the decision at step 305 is affirmative and the controller proceeds
19 to step 307 to discard DA_1, SA_1, FI_1 and move DA_2, SA_2 to
20 storage locations 51, 52 of the register 30, and move FI_2, auxiliary
21 information and payload data from locations 57 to 59 to the left
22 so that FI_2 immediately follows the header information stored in
23 location 53. In this way, an outgoing packet is formulated in the
24 register 31 as shown in Fig. 4B.

25   The controller then forwards the outgoing packet to the
26 output buffer 34 for transmission. Because the storage locations
27 55, 56 and 57 are eliminated, the whole length of the outgoing
28 packet is advantageously shorter than the incoming packet in
29 terms of bandwidth occupied during transmission.

30   Therefore, the destination and source addresses of the
31 source network contained in the incoming packet are converted to
32 the addresses of the destination network.

1   Since time-consuming table search is not required for
2   packets if they contain the address data of their destination
3   network, they experience a minimum latency when they travel
4   from one network to another. Further, the cost of the gateway is
5   reduced due to the elimination of the need to provide costly high
6   speed address conversion.

7   In the previous embodiment, the target addresses cannot be
8   reconverted to the original addresses, and hence the original
9   addresses can no longer be used. However, there may be instances
10   where an intermediate network is interposed between the source
11   and destination networks, and the source and destination
12   networks use the same address format while the intermediate
13   network uses a different address format. In such applications, the
14   original addresses are converted to the target addresses in a first
15   gateway at the boundary between the source and intermediate
16   networks and the target addresses are reconverted to the original
17   addresses in a second gateway at the boundary between the
18   intermediate and destination networks.

19   This is implemented by transposing the original address
20   data and the target address data between different storage location
21   of the register 31 according to a flowchart shown in Fig. 5, in
22   which steps corresponding to those in Fig. 3 are marked with the
23   same numerals as those in Fig. 3 and the description thereof is
24   omitted for simplicity.

25   Fig. 5 differs from Fig. 3 in that if the decision at step 305
26   is affirmative, the routine proceeds to step 501 to transpose DA_1
27   and SA_1 with DA_2 and SA_2 between storage locations 51, 52 and
28   storage locations 55, 56 of the register 31, as shown in Fig. 6A, so
29   that an outgoing packet is formulated in the register as shown in
30   Fig. 6B.

31   It will be seen that when a packet is received in a first
32   gateway from a source network, the address data DA_1 and SA_1 of

1 the source network are converted to the address data DA_2 and
2 SA_2 of an intermediate network and transmitted through the
3 intermediate network to a second gateway. In the second gateway,
4 the address data DA_2 and SA_2 of the intermediate network are
5 reconverted to the address data DA_1 and SA_1 of a destination
6 network and transmitted through the destination network where
7 the packet is routed to a destination terminal.